T COOPERATION TREATY

. 1				
	ŘEC'D		SEP	2004
	200	15		
6	WIPO	,,,		PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference FOR FURTHER ACTION	ON See Form PCT/IPEA/416		
BP105981			
International application No. International filing date (di			
PCT/FI 2003/000370 14-05-2003	31-05-2002		
International Patent Classification (IPC) or national classification and	IPC .		
H04Q 7/38, H04B 7/00	1		
Applicant CORPORATION of all			
NOKIA CORPORATION et al			
 This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 			
2. This REPORT consists of a total of 5 sheets, including this cover sheet.			
3. This report is also accompanied by ANNEXES, comprising:			
The state of the s	requ) a total of 25 sheets, as follows:		
- and the first of the andler of	rewings which have been amended and are the basis of this report		
and/or sheets containing rectifications at	thorized by this Authority (see Rule 70.16 and Section 607 of the		
Administrative Instructions).	t which this Authority considers contain an amendment that goes		
sheets which supersede earlier sneets, or beyond the disclosure in the international	1 application as filed, as indicated in item 4 of Box No. I and the		
Supplemental Box.			
b. (sent to the International Bureau only) a total of	(indicate type and number of electronic carrier(s))		
contrinin	g a sequence listing and/or tables related thereto, in computer		
readable form only, as indicated in the Supplem	ental Box Relating to Sequence Listing (see Section 802 of the		
Administrative Instructions).			
4. This report contains indications relating to the following item	18 :		
Box No. I Basis of the report			
Box No. II Priority	AA 4		
Box No. III Non-establishment of opinion with	n regard to novelty, inventive step and industrial applicability		
Box No. IV Lack of unity of invention			
Box No. V Reasoned statement under Article applicability; citations and explan	35(2) with regard to novelty, inventive step or industrial ations supporting such statement		
Box No. VI Certain documents cited			
Box No. VII Certain defects in the international application			
Box No. VIII Certain observations on the international application			
Date of submission of the demand	Date of completion of this report		
	•		
11-12-2003	26-08-2004		
Name and mailing address of the IPEA/SE	Authorized officer		
Patent- och registreringsverket			
Box 5055 S-102 42 STOCKHOLM	Behroz Moradi /itw		
Forming No. +46. 9. 667. 72. 88	Telephone No. +46 8 782 25 00		

INTERNATIONAL PRELIMIN REPORT ON PATENTABILITY

International application No.	
PCT/F-2003/000370	

Box	No. I	Bas	is of the report	
1.	With r	rise indic	the language, this report is based on the international application in the lated under this item.	
		This rep	ort is based on a translation from the original language into the following language of a translation furnished for the purposes of:	guage,
		П	international search (under Rules 12.3 and 23.1(b))	
		П	publication of the international application (under Rule 12.4)	
			international preliminary examination (under Rules 55.2 and/or 55.3)	
2.	furnisi	hed to th re not an	the elements of the international application, this report is based on (e receiving Office in response to an invitation under Article 14 are referred nexed to this report):	replacement sheets which have been I to in this report as "originally filed"
		the inte	emational application as originally filed/furnished	
	\boxtimes		cription:	as originally filed/furnished
			1-2, 6-21	2004-06-09
		pages*	3, 4, 5	
	N 2	the cla		
			ims:	as originally filed/furnished
	•	pages pages	22-26 as amended (together	with any statement) under Article 19
		pages'	received by this Authority on	
		pages'	received by this Authority on	
	\boxtimes	the dr	awings:	· · · · · · · · · · · · · · · · · · ·
•		pages		as originally filed/furnished
		pages		
	_	pages	ence listing and/or any related table(s) – see Supplemental Box Relating to S	
	Ш	a sequ	ence listing and/or any related table(s) – see supplemental 2011 Notating to 2	3
3.		The a	mendments have resulted in the cancellation of:	
1			the description, pages	
			the claims, Nos.	
l			the drawings, sheets/figs	
			the sequence listing (specify):	
			any table(s) related to the sequence listing (specify):	
4.		This made 70.2(report has been established as if (some of) the amendments annexed to the since they have been considered to go beyond the disclosure as filed, as in (c)).	is report and listed below had not been ndicated in the Supplemental Box (Rule
			the description, pages	
			the claims, Nos.	
			the drawings, sheets/figs	
			the sequence listing (specify):	
			any table(s) related to the sequence listing (specify):	
*	: If ite	ет 4 арр	lies, some or all of those sheets may be marked "superseded."	

Во	k No. V	Reasoned statement un citations and explanati	nder Article 3 ons supportin	55(2) with regard to novelty, inventive step or industrial applicability ng such statement	' ;
1.	Statement				1000
Novelty (N)		Claims	1-27	YES	
	••		Claims		NO
	Invent	ive step (IS)	Claims	1-27	YES
			Claims		NO
	Indust	rial applicability (IA)	Claims	1-27	YES
			Claims		МО

2. Citations and explanations (Rule 70.7)

Documents cited in the International Search Report:

D1: WO 0131958 A1
D2: US 2001008521 A1
D3: EP 0 984 581 A1
D4: US 2002027890 A1
D5: EP 0946076 A2
D6: US 6385437 B1

D7: GB 2314734 A

D1 describes a method for performing a transition from a slotted combined continuous communication mode into a communication mode and measurement mode in a mobile station of a cellular radio system, comprising the steps of: providing a set of certain criteria to be observed during the continuous communication mode; wherein the step of providing a set of criteria comprises the sub step of providing a criterion which is fulfilled if a base station of the cellular radio system seems to be not responding to power control commands asking for more downlink power while preparations for an inter-cell handover are not in progress; observing, whether at least one fulfilled during the is criteria communication mode; and as a response to the fulfilment of at least one of said criteria is fulfilled during the continuous changing the operation of the mobile communication mode, station into the combined slotted communication mode and measurement mode, wherein the step of observing, whether at least one of said criteria is fulfilled during the continuous communication mode, comprises the sub step of observing, whether or not a serving base station is responding to a number of successive power control commands asking for more downlink power, (pages 1-4). .../...

PCT/

2003/000370

Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: $Box\ V$

D2 describes a method for preparing an interfrequency handover of a certain communication connection from a first frequency to a second frequency, the method comprising the following steps of: periodically intermitting the transmission/receipt of data on the first frequency for certain transmission gaps, where the number of transmission gaps is at least one during each transmission period, a certain sequence of transmission periods is used, and at least one transmission period has a having a first duration and a transmission gap second duration, which gap having a transmission duration is different from the first duration, and performing measurements on the second frequency during the transmission Adequate frequency. first the synchronization symbols can be transmitted periodically even when there is increase in transmission power, (page 1 part 1 page 7 part 77).

D3 describes a method for controlling interfrequency handover (=handover between different frequencies) of a mobile station, comprising communication, slotted station compressed), and measurement mode. The mobile station Changes the operation into the combined slotted communication mode and measurement mode for preparing an interfrequency handover, (column 28 parts 138). By establishing the synchronization with another frequency carrier based on detected first and second search codes, interfrequency handover is carried out, and by establishing the synchronization with GSM based on the detected FCCH and SCH, inter communication system handover is carried out. In the transmission in the compressed mode, nontransmission timing is provided in the downlink frame, and can be set to a desired period of time (duration). This nontransmission timing represents idle period during which the strength (= power) of the other frequency carrier is measured. In this way, slotted transmission can be achieved by inserting the idle period during transmission of compressed mode frames. in the compressed mode, the same transmission power as in the normal mode is used to intermittently transmit a compressed frame at a lower transmission rate than in the normal mode; therefore, during a handover between frequencies, the amount of interference power to other users on the same frequency is reduced, whereby a handover between frequencies with reduced interference can be achieved. (Column 3, part 16 - column 19, part 95).

Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: Box $\,\,V\,$

D4 or D5 describe A method of controlling a frequency handover in a wireless communication system in which a mobile station communicates with one or more base stations, the method comprising the steps of: generating a trigger metric as a function of a measure of receive power at the mobile station; and utilizing the trigger metric to control a handoff from a current frequency to a new frequency in an ongoing call, wherein the handoff is performed without utilizing any signal-to-noise measures for pilot signals at the new frequency, (D5 column 2 part 5 - column 3 part 8).

D6 describes a power control method for a mobile station having transmission frames, at least one compressed mode transmission frame including a transmission duration when data is transmitted on a first frequency, and a transmission-off duration for searching another frequency in order to perform an inter-frequency handover, the transmission duration having increased transmission power, the method comprising the steps of: resetting, in a base station, a power control threshold depending on a length of the transmission-off duration; and receiving, in the base station, transmission power-increased data; comparing a power of a received signal with the power control threshold; generating a power-up command when the power control threshold is higher than the received signal power; and generating a power-down command when the power control threshold is lower than the received signal power, (column 4 lines 27 - 61).

The invention defined in claims 1-27 is not disclosed by any of these documents. The cited prior art does not give any indication that would lead a person skilled in the art to the claimed method of providing a flexible and straightforward method for controlling interfrequency handovers by comparing the quality of the communication connection to target value based on an interference control of the communication connection, wherein the target value depends on the quality target value used in downlink outer loop power control of the communication connection. Therefore, the invention defined in claims 1-27 is not obvious to a person skilled in the art. Accordingly, the invention defined in claims 1-27 is novel and is considered to involve an inventive step. The invention defined in claims 1-27 is industrially applicable.

D7 describes the prior art of the invention.